

EH320UST

1080p Ultra Short Throw **Projector**

- Bright projection 4000 ANSI lumens
- Full HD 1080p resolution, 20,000:1 contrast ratio
- 2x HDMI input and 16W audio
- Crestron RoomView® RJ45 control and monitoring





















EH320UST

Optoma's 1080p ultra short throw projector, the EH320UST, is perfect for businesses, schools and colleges. It is bright (4,000 lumens) and a throw ratio of 0.25:1 means that it can project a 100" image from just 55cm away. And having the projector installed so close to the screen avoids any shadows being cast across the screen from the presenter(s).

It provides a complete package for engaging learning with many new features, including two HDMI inputs, powered USB port, powerful 16W built-in speaker, improved lamp life, compact chassis and a completely new mounting system for a fast and simple set-up.

Ultra short throw



With an ultra-short throw lens, you can project an impressive image greater than 100" from just 55cm away. This allows you to place the projector closer to the wall, reducing shadows so you can present with ease; perfect for interactive applications.

Full HD 1080p

1080p resolution gives you sharp and detailed images from HD content without downscaling or compression; perfect for watching movies, viewing photos and documents.



High Contrast

Add more depth to your image with a high contrast projector; with brighter whites and ultra-rich blacks, images come alive and text appears crisp and clear - ideal for business and education applications.

Full 3D

Optoma projectors can display true 3D content from almost any 3D source, including 3D Blu-ray players, 3D broadcasting and the latest generation games consoles. Support for 144Hz rapid refresh rate provides ultra-smooth flicker free images.



Integrated Speaker

The built-in speaker offers excellent audio support. Easy to set up without the need for costly external speakers

Eco+



Eco+ technology brings together high contrast, improved lamp life and energy saving features that are easy to use while reducing power consumption.

Energy Saving

Using the specially designed lamp modes, you can reduce the power consumption by up to 70%. Each mode also has a positive effect on the lamp life, while lowering the total cost of ownership and reducing maintenance.

Quick Resume

This feature allows the projector to be instantly powered on again, if it is accidentally switched off.

Auto power off

There may be instances when the projector is left running when not in use. To help save energy if the projector is left running and no source is detected, the "Auto power off" feature automatically turns off the projector after a set period of time.

Eco AV Mute

Stay in control of your presentation with Eco AV mute. Direct your audience's attention away from the screen by blanking the image when no longer needed. This also reduces the power consumption by up to 70%, further prolonging the life of your lamp.

Long Lamp Life

Reduce the number of lamp changes with lamp life of up to 6500 hours

Upgrade your EPSON® UST projector to 1080p

Upgrade your EPSON® ultra short throw projector with an Optoma 1080p UST projector for higher resolution - without changing your existing mount or white board.



Remote Mouse

Keep your audience's attention focussed on the right things using the simple, yet powerful remote with USB mouse control.

Networking and Control

Featuring a wide range of options you can remotely control and monitor the projector.

- RS232 Optoma projector's come with an extensive set of RS232 commands making it simple and easy to manage using any control system.
- AMX Compatibility Dynamic discovery protocol is incorporated into the projector allowing for easy installation with AMX control systems.
- LAN Control Using the compatible RoomView® software you can power on/off, monitor, manage and control up to 250 projectors at the same time from any computer.
 - Schedule the projectors to power on/off.
 - Control and alter the projector settings using the simple web browser.
 - Emergency text broadcast capabilities for urgent or important announcements.
 - Automatically receive email updates for lamp maintenance.







Colour Guarantee

We are so confident that the image colour quality will remain as good as the day you bought it that Optoma will guarantee it for five years.





Amazing Colour

Give powerful presentations and educational lessons with stunning colours. Optoma projectors provide you with reliable colour performance suitable for any content and environment. From accurate sRGB colours for true life like images to vibrant punchy presentations. We have a display mode to specific meet your needs.





Wireless Presenting (optional extra)

Making presentations couldn't be easier using the optional wireless features of the WPS Wireless Adapter (sold separately) - you can connect and display presentations wirelessly from a laptop, PC or mobile device.



USB Power

Use the USB-Power to power an HDMI dongle, such as Google Chromecast or the Optoma WHD200 wireless HDMI device.

EH320UST Specification

Native Resolution	Display Technology	Single 0.65" DarkChip 3 1080p DLP® Technology by Texas Instruments
Contrast	_ , , ,	0 , ,
Lamp Life ² Eco+/Dynamic/Eco/Bright 6500/5000/5000/3000 (hrs) Throw Ratio 0,25:1 Zoom Type Fixed I/O Connectors 2 x HDMI (14 a 3D support), 2 x VGA (YPbPr/RGB), Composite, 2 x Audio in 3.5mm, Audio Out 3.5mm, VGA Out (Sha VGA2), RJ45, RS232, USB remote mouse/service, 12V trigger, Mic In, USB-A Power, 3D-Sync Speaker 16 Keystone Correction ± 5* Vertical Weight (kg) 4,78 Dimensions (W x D x H) (mm) 385 x 310 x 120 Aspect Ratio 16:9 Native, 4:3 Compatible Offset 118% Projection Distance 0,45 - 0.59m Projection Compatibility UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac Uniformity 85% Computer Compatibility UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac Video Compatibility UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac Video Compatibility PAL (B, D, G, H, I, M, N, 576/lp), NTSC (M, 4.43/3.58 MHz, 480/lp), SECAM (B, D, G, K, K1, L) HD (1080), 720p) Full 30 - The 3D features of Optoma projectors can only be used with compatible 30 content. Typical applications including the Systems, 3D TV broadcast systems, (SKY in the UK), 80-43 y 3D ⁻¹¹ and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4 sepcification. 3D Compatibility Side-Psy-Side:1880160 / 60, 720p50 / 60 Frame-pack: 1880p24, 720p50 / 60 Horizontal Scan Rate 15.3 - 91.1kHz Vertical Scan Rate 24 - 854x (120±1 for 3D) Displayable Colours 1.07 Billion Noise Level (Eco mode) 288B Power Supply 100-240V, 50-60Hz Power Consumption 310W Bright mode / 260W Eco mode (< 0.5W Standby) Lamp Type 260W Operating Conditions 5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m Security Security As Kensington lock, password protection.	Brightness ¹ (Bright Mode)	4000 ANSI Lumens
Throw Ratio Contractor Fixed Computer Compute	Contrast	20,000:1
Throw Ratio Contractor Fixed Computer Compute	Lamp Life ² Fco+/Dynamic/Fco/Bright	6500/5000/5000/3000 (hrs)
Zoom Type		` '
2 x HDMI (1.4a 3D support), 2 x VGA (YPbPr/RGB), Composite, 2 x Audio In 3.5mm, Audio Out 3.5mm, VGA Out (Sha VGA2), RJA5, RS232, USB remote mouse/service, 12V trigger, Mic In, USB-A Power, 3D-Sync Speaker		
VGA2), RJ45, RS232, USB remote mouse/service, 12V trigger, Mic In, USB-A Power, 3D-Sync		
Keystone Correction ± 5° Vertical Weight (kg) 4.78 Dimensions (W x D x H) (mm) 385 x 310 x 120 Aspect Ratio 15:9 Native, 4:3 Compatible Offset 118% Projection Screen Size 2.03 − 2.54m (80° − 100°) Diagonal 16:9 Projection Distance 0.45 - 0.59m Projection Lens F/2.4; Fa3.72mm, Fixed Zoom Uniformity 85% Computer Compatibility UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac Video Compatibility PAL (B, D, G, H, I, M, N, 576i/p), NTSC (M, 4.43/3.58 MHz, 480i/p), SECAM (B, D, G, K, K1, L) HD (1080i, 720p) 3D Support Full 30 - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications inclusion with 3D educational or 3D design and modelling systems, 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D™ and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4s specification. 3D Compatibility Side-yS-side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Horizontal Scan Rate 15.3 - 91.1kHz Vertical Scan Rate 24 - 85Hz (120Hz for 3D) Displayable Colours 1.07 Billion Noise Level (Eco mode)	I/O Connectors	
Weight (kg) 4.78 Dimensions (W x D x H) (mm) 385 x 310 x 120 Aspect Ratio 16:9 Native, 4:3 Compatible Offset 118% Projection Screen Size 2.03 - 2.54m (80° - 100°) Diagonal 16:9 Projection Distance 0.45 - 0.59m Projection Lens F/2.4; Fs.3.72mm, Fixed Zoom Uniformity 85% Computer Compatibility UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac Video Compatibility PAL (B, D, G, H, I, M, N, 576i/p), NTSC (M, 4.43/3.58 MHz, 480i/p), SECAM (B, D, G, K, K1, L) HD (1080i, 720p) 3D Support Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications inclured with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D™ and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4s specification. 3D Compatibility Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Fore-Full 3Can Rate 15.3 - 91.1kHz Vertical Scan Rate 24 - 85Hz (120Hz for 3D) Displayable Colours 1.07 Billion Noise Level (Eco mode) 28dB Power Consumption 310W Bright mode / 260W Eco mode (< 0.5W Standby) </td <td>· · · · · · · · · · · · · · · · · · ·</td> <td></td>	· · · · · · · · · · · · · · · · · · ·	
Dimensions (W x D x H) (mm) 385 x 310 x 120 Aspect Ratio 16:9 Native, 4:3 Compatible Offset 118% Projection Screen Size 2.03 – 2.54m (80" – 100") Diagonal 16:9 Projection Distance 0.45 - 0.59m Projection Lens F/2.4; f=3.72m, Fixed Zoom Uniformity 85% Computer Compatibility UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac Video Compatibility PAL (B, D, G, H, I, M, N, 576i/p), NTSC (M, 4.43/3.58 MHz, 480i/p), SECAM (B, D, G, K, K1, L) HD (1080i, 720p) 3D Support Full 3D - The 3D features of Optoma protectors can only be used with compatible 3D content. Typical applications incluwith 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D™ and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4s specification. 3D Compatibility Side-by-Side: 1080150 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Horizontal Scan Rate 15.3 - 91.1kHz Vertical Scan Rate 24 - 85Hz (120Hz for 3D) Displayable Colours 1.07 Billion Noise Level (Eco mode) 28dB Power Consumption 310W Bright mode / 260W Eco mode (< 0.5W Standby)		± 5° Vertical
Aspect Ratio Offset 118% Projection Screen Size 2.03 − 2.54m (80" − 100") Diagonal 16:9 Projection Distance 0.45 - 0.59m Frigetion Distance 0.45 - 0.59m Frigetion Lens Friz 4; f=3.72mm, Fixed Zoom Uniformity 85% Computer Compatibility UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac Video Compatibility PAL (B, D, G, H, I, M, N, 576ip), NTSC (M, 4.43/3.58 MHz, 480i/p), SECAM (B, D, G, K, K1, L) HD (1080i, 720p) 3D Support Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content Typical applications inclu with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D™ and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4s specification. 3D Compatibility Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Horizontal Scan Rate 15.3 - 91.1kHz Vertical Scan Rate 24 - 85Hz (120Hz for 3D) Displayable Colours 1.07 Billion Noise Level (Eco mode) 28dB Power Consumption 310W Bright mode / 260W Eco mode (< 0.5W Standby) Lamp Type 260W Operating Conditions 5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m 5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m 5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m 5°C Languages: English, German, French, Italian, Spanish, Portuguese, Swedish, Dutch, Norwegian/Danish, Polish, Rus	Weight (kg)	4.78
Offset 118% Projection Screen Size 2.03 – 2.54m (80" – 100") Diagonal 16:9 Projection Distance 0.45 - 0.59m Projection Lens F72.4; f=3.72mm, Fixed Zoom Uniformity 85% Computer Compatibility UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac Video Compatibility PAL (B, D, G, H, I, M, N, 576i/p), NTSC (M, 4.43/3.58 MHz, 480i/p), SECAM (B, D, G, K, K1, L) HD (1080i, 720p) 3D Support Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications inclu with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D™ and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4c specification. 3D Compatibility Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Horizontal Scan Rate 15.3 - 91.1kHz Vertical Scan Rate 24 - 85Hz (120Hz for 3D) Displayable Colours 1.07 Billion Noise Level (Eco mode) 28dB Power Consumption 310W Bright mode / 260W Eco mode (< 0.5W Standby)	Dimensions (W x D x H) (mm)	385 x 310 x 120
Projection Screen Size 2.03 – 2.54m (80" – 100") Diagonal 16:9 Projection Distance 0.45 - 0.59m Projection Lens F/2.4; f=3.72mm, Fixed Zoom Uniformity 85% Computer Compatibility UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac Video Compatibility PAL (B, D, G, H, I, M, N, 576i/p), NTSC (M, 4.43/3.58 MHz, 480i/p), SECAM (B, D, G, K, K1, L) HD (1080i, 720p) 3D Support Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications inclu with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D™ and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4c specification. 3D Compatibility Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Horizontal Scan Rate 15.3 - 91.1kHz Vertical Scan Rate 24 - 85Hz (120Hz for 3D) Displayable Colours 1.07 Billion Noise Level (Eco mode) 28dB Power Consumption 310W Bright mode / 260W Eco mode (< 0.5W Standby)	Aspect Ratio	16:9 Native, 4:3 Compatible
Projection Distance Projection Lens Fr/2.4; f=3.72mm, Fixed Zoom Uniformity 85% Computer Compatibility UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac Video Compatibility PAL (B, D, G, H, I, M, N, 576i/p), NTSC (M, 4.43/3.58 MHz, 480i/p), SECAM (B, D, G, K, K1, L) HD (1080i, 720p) 3D Support Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications inclu with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D™ and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4s specification. 3D Compatibility Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Horizontal Scan Rate 15.3 - 91.1kHz Vertical Scan Rate 15.3 - 91.1kHz Vertical Scan Rate 24 - 85Hz (120Hz for 3D) Displayable Colours 1.07 Billion Noise Level (Eco mode) 28dB Power Supply 100-240V, 50-60Hz Power Consumption 310W Bright mode / 260W Eco mode (< 0.5W Standby) Lamp Type 260W Operating Conditions 5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m Security Security Security bar, Kensington lock, password protection On Screen Display	Offset	118%
Projection Lens F/2.4; f=3.72mm, Fixed Zoom Uniformity 85% Computer Compatibility UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac Video Compatibility PAL (B, D, G, H, I, M, N, 576i/p), NTSC (M, 4.43/3.58 MHz, 480i/p), SECAM (B, D, G, K, K1, L) HD (1080i, 720p) 3D Support Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications inclusion with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D™ and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4s specification. 3D Compatibility Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Horizontal Scan Rate 15.3 - 91.1kHz Vertical Scan Rate 24 - 85Hz (120Hz for 3D) Displayable Colours 1.07 Billion Noise Level (Eco mode) 28dB Power Supply 100-240V, 50-60Hz Power Consumption 310W Bright mode / 260W Eco mode (< 0.5W Standby) Lamp Type 260W Operating Conditions 5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m Security Security Security bar, Kensington lock, password protection On Screen Display	Projection Screen Size	2.03 – 2.54m (80" – 100") Diagonal 16:9
Uniformity 85% Computer Compatibility UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac Video Compatibility PAL (B, D, G, H, I, M, N, 576i/p), NTSC (M, 4.43/3.58 MHz, 480i/p), SECAM (B, D, G, K, K1, L) HD (1080i, 720p) 3D Support Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications incluwith 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D™ and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4e specification. 3D Compatibility Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Horizontal Scan Rate 15.3 - 91.1kHz Vertical Scan Rate 24 - 85Hz (120Hz for 3D) Displayable Colours 1.07 Billion Noise Level (Eco mode) 28dB Power Supply 100-240V, 50-60Hz Power Consumption 310W Bright mode / 260W Eco mode (< 0.5W Standby) Lamp Type 260W Operating Conditions 5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m Security Security Security Security bar, Kensington lock, password protection On Screen Display	Projection Distance	0.45 - 0.59m
Computer Compatibility UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac Video Compatibility PAL (B, D, G, H, I, M, N, 576i/p), NTSC (M, 4.43/3.58 MHz, 480i/p), SECAM (B, D, G, K, K1, L) HD (1080i, 720p) Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications incluwith 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D™ and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4s specification. 3D Compatibility Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Horizontal Scan Rate 15.3 - 91.1kHz Vertical Scan Rate 24 - 85Hz (120Hz for 3D) Displayable Colours Noise Level (Eco mode) 28dB Power Supply 100-240V, 50-60Hz Power Consumption 310W Bright mode / 260W Eco mode (< 0.5W Standby) Lamp Type 260W Operating Conditions 5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m Security Security bar, Kensington lock, password protection On Screen Display	Projection Lens	F/2.4; f=3.72mm, Fixed Zoom
Video CompatibilityPAL (B, D, G, H, I, M, N, 576i/p), NTSC (M, 4.43/3.58 MHz, 480i/p), SECAM (B, D, G, K, K1, L) HD (1080i, 720p)3D SupportFull 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications inclu with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D™ and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification.3D CompatibilitySide-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60Horizontal Scan Rate15.3 - 91.1kHzVertical Scan Rate24 - 85Hz (120Hz for 3D)Displayable Colours1.07 BillionNoise Level (Eco mode)28dBPower Supply100-240V, 50-60HzPower Consumption310W Bright mode / 260W Eco mode (< 0.5W Standby)	Uniformity	85%
Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications incluwith 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D m and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4s specification. 3D Compatibility Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Horizontal Scan Rate 15.3 - 91.1kHz Vertical Scan Rate 24 - 85Hz (120Hz for 3D) Displayable Colours 1.07 Billion Noise Level (Eco mode) 28dB Power Supply 100-240V, 50-60Hz Power Consumption 310W Bright mode / 260W Eco mode (< 0.5W Standby) Lamp Type 260W Operating Conditions 5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m Security Security bar, Kensington lock, password protection On Screen Display 5°Languages: English, German, French, Italian, Spanish, Portuguese, Swedish, Dutch, Norwegian/Danish, Polish, Rus	Computer Compatibility	UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D™ and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4s specification. 3D Compatibility Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Horizontal Scan Rate 15.3 - 91.1kHz Vertical Scan Rate 24 - 85Hz (120Hz for 3D) Displayable Colours 1.07 Billion Noise Level (Eco mode) 28dB Power Supply 100-240V, 50-60Hz Power Consumption 310W Bright mode / 260W Eco mode (< 0.5W Standby) Lamp Type 260W Operating Conditions 5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m Security Security bar, Kensington lock, password protection On Screen Display 25 Languages: English, German, French, Italian, Spanish, Portuguese, Swedish, Dutch, Norwegian/Danish, Polish, Rus.	Video Compatibility	PAL (B, D, G, H, I, M, N, 576i/p), NTSC (M, 4.43/3.58 MHz, 480i/p), SECAM (B, D, G, K, K1, L) HD (1080i, 720p)
Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Horizontal Scan Rate	3D Support	Blu-ray 3D™ and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a
Vertical Scan Rate 24 - 85Hz (120Hz for 3D) Displayable Colours 1.07 Billion Noise Level (Eco mode) 28dB Power Supply 100-240V, 50-60Hz Power Consumption 310W Bright mode / 260W Eco mode (< 0.5W Standby) Lamp Type 260W Operating Conditions 5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m Security Security bar, Kensington lock, password protection On Screen Display 25 Languages: English, German, French, Italian, Spanish, Portuguese, Swedish, Dutch, Norwegian/Danish, Polish, Rus	3D Compatibility	Frame-pack: 1080p24, 720p50 / 60
Displayable Colours 1.07 Billion Noise Level (Eco mode) 28dB Power Supply 100-240V, 50-60Hz Power Consumption 1310W Bright mode / 260W Eco mode (< 0.5W Standby) Lamp Type 260W Operating Conditions 5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m Security Security Security bar, Kensington lock, password protection On Screen Display 25 Languages: English, German, French, Italian, Spanish, Portuguese, Swedish, Dutch, Norwegian/Danish, Polish, Rus	Horizontal Scan Rate	15.3 - 91.1kHz
Noise Level (Eco mode) Power Supply 100-240V, 50-60Hz Power Consumption 310W Bright mode / 260W Eco mode (< 0.5W Standby) Lamp Type 260W Operating Conditions 5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m Security Security Security bar, Kensington lock, password protection On Screen Display 25 Languages: English, German, French, Italian, Spanish, Portuguese, Swedish, Dutch, Norwegian/Danish, Polish, Rus	Vertical Scan Rate	24 - 85Hz (120Hz for 3D)
Power Supply 100-240V, 50-60Hz Power Consumption 310W Bright mode / 260W Eco mode (< 0.5W Standby) Lamp Type 260W Operating Conditions 5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m Security Security Security bar, Kensington lock, password protection On Screen Display 25 Languages: English, German, French, Italian, Spanish, Portuguese, Swedish, Dutch, Norwegian/Danish, Polish, Rus	Displayable Colours	1.07 Billion
Power Consumption 310W Bright mode / 260W Eco mode (< 0.5W Standby) Lamp Type 260W Operating Conditions 5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m Security Security Security Security bar, Kensington lock, password protection On Screen Display 25 Languages: English, German, French, Italian, Spanish, Portuguese, Swedish, Dutch, Norwegian/Danish, Polish, Rus	Noise Level (Eco mode)	28dB
Lamp Type 260W Operating Conditions 5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m Security Security Security bar, Kensington lock, password protection On Screen Display 25 Languages: English, German, French, Italian, Spanish, Portuguese, Swedish, Dutch, Norwegian/Danish, Polish, Rus	Power Supply	100-240V, 50-60Hz
Operating Conditions 5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m Security Security Security bar, Kensington lock, password protection On Screen Display 25 Languages: English, German, French, Italian, Spanish, Portuguese, Swedish, Dutch, Norwegian/Danish, Polish, Rus	Power Consumption	310W Bright mode / 260W Eco mode (< 0.5W Standby)
Security Security Security bar, Kensington lock, password protection On Screen Display 25 Languages: English, German, French, Italian, Spanish, Portuguese, Swedish, Dutch, Norwegian/Danish, Polish, Rus	Lamp Type	260W
On Screen Display 25 Languages: English, German, French, Italian, Spanish, Portuguese, Swedish, Dutch, Norwegian/Danish, Polish, Rus	Operating Conditions	5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m
	Security	Security bar, Kensington lock, password protection
Romanian, Slovenian	On Screen Display	25 Languages: English, German, French, Italian, Spanish, Portuguese, Swedish, Dutch, Norwegian/Danish, Polish, Russian, Finnish, Greek, Hungarian, Czech, Arabic, Traditional Chinese, Simplified Chinese, Japanese, Korean, Thai, Turkish, Farsi, Romanian, Slovenian
Standard Accessories AC power cord, remote control, battery, quick start card, CD user manual	Standard Accessories	
Optional Accessories DLP® Link™ 3D glasses, wireless, wall mount	Optional Accessories	DLP® Link™ 3D glasses, wireless, wall mount
Optional Wireless Yes	Optional Wireless	Yes
RoHS Compliant	RoHS	Compliant



Optoma Europe Ltd. 42 Caxton Way, Watford Business Park, Watford, Hertfordshire, UK. WD18 8QZ www.optoma.co.uk

¹Lamp based projectors brightness and lifetime will vary depending on selected projector mode, environmental conditions and usage. As is common with all lamp based projectors, brightness will decrease over the lamp lifetime. LED projectors do not have a replaceable lamp and the brightness does not decay significantly over the product lifetime.

 2 Typical lamp life achieved through testing. Will vary according to operational use and environmental conditions

08/10/2016 17:11