

# PA240

Class G Power Amplifier

# ARCAM



## Features

- 2 Channel Power Amplifier
- 2 x 380W Class G amplification
- 1 x 790W Class G bridged mode
- Class G amplification with 50W of class A operation
- Toroidal transformer
- Stereo, Dual Mono or Bridged operation
- Ethernet, RS232 control
- Switchable RCA or balanced XLR inputs

## Exceptional Power, Immersive Sound

The PA240 is a high-performance power amplifier that delivers 2 channels of efficient Class G amplification. With an impressive 380W per channel, the PA240 is designed to offer the greatest flexibility and power without compromising on control.

Featuring the best-in-class components including a toroidal based power supply, acoustically damped chassis, paralleled transistor output stages and exceptionally low levels of distortion, the PA240 masters the reproduction of music with all its originality and detail for an unmatched level of sound quality and clarity.

# PA240

Class G Power Amplifier

# ARCAM

Continuous power output at 0.2% THD per channel		
2 channels driven, 4Ω / 8Ω, 20Hz – 20kHz	380W/225W	
1 channel driven, 8Ω bridged mode, 20-20kHz	790W	
Harmonic distortion, 80% power, 8Ω at 1kHz	0.001%	
Inputs		
	RCA Type	XLR Type
Input sensitivity 200W / 8Ω	1.15V RMS	2.3V RMS
Signal/Noise ratio (A-wtd) 50W / 8Ω	110dB	
Input impedance	10kΩ	
Frequency response	20 - 20kHz +/-0.05dB	
General		
Mains voltage	110–120V or 220–240V, 50–60Hz	
Power consumption (maximum)	1.5kW	
Power consumption (idle, typical)	90W (Thermal dissipation approx. 340 BTU/hour)	
Power consumption (standby)	<0.5W	
Dimensions W x D x H (including feet, control knob and speaker terminals)	433 x 425 x 177mm	
Weight (net)	18kg	
Weight (packed)	19.7kg	
EAN	6925281956768	

