## 8" Two-Way In-Wall Surround Loudspeaker



## KS-7800-THX

Developed to bring a whole new dimension of reality to home theater, the Klipsch KS-7800-THX offers the ultimate surround sound performance in a flush-mount design.

Because of its THX® Ultra2 certification, the KS-7800-THX works well with movie presentations playing up to reference levels in rooms of 3,000 cubic feet or larger.

The KS-7800-THX is also capable of delivering the same high-output, low distortion signature sound as its traditional enclosure counterpart, the KS-525-THX. It employs an 8-inch aluminum woofer and a patent-pending horn array, consisting of two vertically-stacked Tractrix Horn-loaded tweeters.

In order to create enveloping sound fields and precise localization of individual effects, this speaker also utilizes Klipsch's Wide Dispersion Surround Technology<sup>™</sup>. Also referred to as WDST, this no-compromise approach gives the KS-7800-THX much more placement flexibility than conventional designs.

Featuring an integrated back box enclosure, the KS-7800-THX's response is both predictable and repeatable. Because this enclosure fits easily within the loudspeaker's footprint, the KS-7800-THX can be installed into new or existing construction.

Combine this dynamic loudspeaker with Klipsch's KL-7800-THX LCR speaker, KW-120-THX subwoofer and KA-1000-THX subwoofer amplifier to create a variety of THX Ultra2 in-wall system configurations. The KS-7800-THX can also be mixed and matched with the Klipsch THX Ultra2 traditional box products.

## S P E C I F I C A T I O N S

$80$ Hz- $20$ kHz $\pm$ 3dB
90dB @ 2.83 volts / 1 meter
8 ohms
2130Hz
100 w max continuous (400 w peak)
Sealed Enclosure
Two-way system using two 1" (2.5cm)
Titanium dome neodymium tweeters in a
diffuse Tractrix horn array and an 8"
Aluminum Cone Woofer
12
17 lbs. (7.7kg)
20.8" (52.7cm)
11.8" (29.8cm)
3.7" (9.4cm)
19" (48.3cm) × 10" (25.4cm)
White with Brushed Aluminum Fascia
IK-802-W (sold separately)



www.klipsch.com I-800-KLIPSCH