



KS-7502-THX

- Brings superior sound to larger rooms
- Delivers a smooth broad distribution of sound
- Maximum installation reliability
- Mix and match with our other THX Ultra2 models

Our top-of-the-line in-ceiling surround speaker, the KS-7502-THX uses highly respected certification, patented technology and premium materials to deliver compelling audio experiences that are second to none. In fact, most in-ceiling surrounds can't "fool" listeners into believing the sound is coming from all around them, rather than from above. But that's not a problem for the KS-7502-THX, as it offers a smooth, seamless broad distribution of sound.

The KS-7502-THX employs dual 5.25-inch Cerametallic woofers that operate in an enclosed tuned-port chamber. These exclusive woofer cones offer superb damping characteristics that will not flex or resonate at frequencies within the drivers' operating ranges, resulting in consistent bass response regardless of the installation or ceiling air space.

Dual 1-inch titanium horn-loaded tweeters lie in a patented vertically stacked Wide Dispersion Surround Technology array, producing enveloping surround performances and precise localization of individual effects.

Adding to its first-class sound, the KS-7502-THX also has a premium look and feel with its grille off, featuring a deluxe MDF baffle with aluminum fascia. But when covered, the speaker's paintable grille allows it to blend in perfectly with any home décor. All-new sure-grip mounting dogs offer even pressure against drywall for long-term installation reliability.

Furthermore, the KS-7502-THX comes with a lot of options. It is timbre matched to all of our THX Ultra2-certified products, so you can mix and match for the discreet stereo or home theater system that's just right for you.

SPECIFICATIONS

Bandwidth	45 Hz - 20 kHz \pm 3dB
Sensitivity	93 dB
Nominal Impedance	4 Ohms
Cross Over Frequency	2500 Hz
Power Handling	60 Watts Cont. 240 Watts Peak
Enclosure Type	Bass Reflex via 1.6" diameter port - Front Flush with Ceiling
Drive Components	Two-way system utilizing two 1" Titanium tweeters in vertically stacked tractrix horns, and Two 5.25" Cerametallic Woofers Utilizes Klipsch's Wide Dispersion Surround Technology™
Weight	11lbs. / 5.0Kg
Height	15.25 in / 38.7cm
Width	0 in / 0.0cm
Depth	9.5 in / 24.1cm
Cutout Height	13.25 in / 33.7cm
Cutout Width	13.25 in / 33.7cm
Material	0.16 in / 4.0mm ABS
Finish	White - Paintable

www.klipsch.com
1-800-KLIPSCH

All specifications are subject to change without notice. ©2008

